

According to Regulation (EU) No 2020/878

### SECTION 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : SHELL TYRE REPAIR
Product code : CRX434, 30462; AT61B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Application : SU21 Consumer product. PC0 Other. Other vehicle (all types) cleaning and care products.

1.3. Details of the supplier of the safety data sheet

Supplier : Kemetyl Kimya Sanayi ve Ticaret Limited Sirketi

Küçükbakkalköy Mah. Dereboyu Cad. Brandium AVYM R5

Blok D:82 Ataşehir / Istanbul, Turkey

Telephone : +908503030587
E-mail : msds@kemetyl.com
Website : www.kemetyl.com

1.4. Emergency telephone number

EMERGENCY TELEPHONE NUMBER, for DOCTORS/FIRE BRIGADE/POLICE only:

TR - Telephone : +908503030587 (During office hours only)

### SECTION 2 HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

CLP classification (1272/2008/EC)

: Aerosols, category 1. Eye irritation, category 2. Specific target organ toxicity after single exposure, category 3. Reproductive toxicity, Additional category, Effects on or via lactation. Hazardous to the aquatic environment — Acute category 1. Hazardous to the aquatic environment — Chronic category 2.

Human health hazards

: Causes serious eye irritation. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking. May cause harm to breast-fed children. Exposure to high vapour concentrations may result in a narcotic effect. Use only as directed. Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal.

Physical/chemical hazards :

Extremely flammable. Keep away from sources of ignition — No smoking. Do not spray on a naked flame or any incandescent material. Do not spray near fire, sources of heat or live electrical equipment. Aerosol may explode from internal pressure build-up when exposed to temperatures exceeding 50 °C.

Environmental hazards

Very toxic to aquatic organisms. Toxic to aquatic life with long lasting effects.

Other information

Caution: Do not breathe spray. Use only in well-ventilated areas. Spray in short intervals for a short period only. Ventilate well after use. Harmful to house pets. Replace the gas in the tyre by air as soon as possible. User should inform repairman of flammable contents. Caution, propellant is flammable, replace only in open air.

### 2.2. Label elements

Label elements (1272/2008/EC):

Hazard pictograms :







Product name : Shell Tyre Repair Page 1/14

Date of issue : 2022-04-08 Replaces issue dated : 2020-05-06 INFO CARE SDS



Kemetyl

### Safety data sheet

According to Regulation (EU) No 2020/878

Signal word : Danger

H- and P-phrases : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H362 May cause harm to breast-fed children.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P263 Avoid contact during pregnancy/while nursing.

P391 Collect spillage.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container to an official chemical waste depot.

Labelling of packagings where the contents do not exceed 125 ml and it is technically impossible to list all phrases:

Hazard pictograms :







Signal word : Danger

H- and P-phrases : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.
 H336 May cause drowsiness or dizziness.
 H362 May cause harm to breast-fed children.

EUH066 Repeated exposure may cause skin dryness or cracking.

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P263 Avoid contact during pregnancy/while nursing.

P391 Collect spillage.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container to an official chemical waste depot.

Additional labelling (for all packaging sizes)

: Contains: n-Butyl acetate; Butanone; Acetone.

: 5 per cent of the mixture consists of component(s) of unknown acute inhalation toxicity.

2.3. Other hazards

Other information : The classification of this product is based on the non-aerosolised form of the mixture (on basis of

section 1.1.3.7. of Regulation (EC) No 1272/2008). There are no data about the product available.

Contains SVHC substances. See section 3.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Product name : Shell Tyre Repair Page 2/14

Date of issue : 2022-04-08 Replaces issue dated : 2020-05-06 INFO CARE SDS



According to Regulation (EU) No 2020/878

#### 3.2. Mixtures

Product description : Mixture. Ingredients which are persistent, bioaccumulative and toxic (PBT) or very persistent and

very bioaccumulative (vPvB) in accordance with the criteria set out in Annex XIII of Regulation (EC)

No 1907/2006: Alkanes, C14-17, chloro

#### Information on hazardous substances:

Substance name	Concentration	CAS nr.	EC number	Remark	REACH nr.
	(w/w) (%)				
Dimethyl ether	25 - < 50	115-10-6	204-065-8		01-2119472128-37
n-Butyl acetate	20 - < 25	123-86-4	204-658-1		01-2119485493-29
Butanone	10 - < 20	78-93-3	201-159-0		01-2119457290-43
Acetone	10 - < 20	67-64-1	200-662-2		01-2119471330-49
Alkanes, C14-17, chloro	2,5 - < 5	85535-85-9	287-477-0	PBT,vPvB	01-2119519269-33

Substance name	Hazard Class	H-phrases	Pictograms	
Dimethyl ether	Flam. Gas 1A; Press.	H220; H280	GHS02	
	Gas			
n-Butyl acetate	Flam. Liq. 3; STOT SE	H226; H336; EUH066	GHS02; GHS07	
	3			
Butanone	Flam. Liq. 2; Eye Irrit.	H225; H319; H336;	GHS02; GHS07	
	2; STOT SE 3	EUH066		
Acetone	Flam. Liq. 2; Eye Irrit.	H225; H319; H336;	GHS02; GHS07	
	2; STOT SE 3	EUH066		
Alkanes, C14-17, chloro	Lact.; Aquatic Acute 1;	H362; H400; H410;	GHS09	M (acute) = 100
	Aquatic Chronic 1	EUH066		M (chronic) = 1

Occupational exposure limit(s), if relevant, are listed in section 8.

Reference is made to chapter 16 for full text of each relevant H phrase.

### SECTION 4 FIRST-AID MEASURES

### 4.1. Description of first aid measures

First aid measures

Inhalation : Move victim into fresh air. Consult a doctor.

Skin contact : Take off contaminated clothing. Wash off skin with plenty of water and soap before product dries up.

Consult a doctor if irritation persists.

Eye contact : Wash out with (lukewarm) water. Remove contact lenses. Consult a doctor.

Ingestion : Aerosol or mist: Ingestion is unlikely to occur.

### 4.2. Most important symptoms and effects, both acute and delayed

Effects and symptoms

Inhalation : May cause headache, drowsiness, dizziness and a feeling of sickness. May cause irritation to

respiratory airways and coughing.

Skin contact : Repeated exposure may cause skin dryness or cracking.

Eye contact : Irritant. May cause redness and pain.

Ingestion : May cause a feeling of sickness, vomiting and diarrhoea.

### 4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians : None known.

### SECTION 5 FIRE-FIGHTING MEASURES

Product name : Shell Tyre Repair Page 3/14

Date of issue : 2022-04-08 Replaces issue dated : 2020-05-06 INFO CARE SDS



According to Regulation (EU) No 2020/878

### 5.1. Extinguishing media

Extinguishing media

Suitable : Carbondioxide (CO2). Alcohol resistant foam. Dry chemical. Water fog.

Not suitable : Water jet. Use of heavy stream of water may spread fire.

#### 5.2. Special hazards arising from the substance or mixture

Special exposure hazards : Aerosol may explode from internal pressure build-up when exposed to temperatures exceeding 50

°C. Do not expose emergency personnel to overheated aerosol containers. Water may be used to

cool container and prevent explosion of the aerosol.

Hazardous thermal decomposition products

: Carbon monoxide may be evolved if incomplete combustion occurs.

### 5.3. Advice for firefighters

Special protective equipment for fire-fighters

: Fight a fire where aerosols are involved from a protected position. Wear full protective clothing and

self-contained breathing apparatus.

### SECTION 6 ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions : Danger of slipping. Clean up spills immediately. Wear shoes with non-slip soles. Avoid contact

with spilled or released material. Do not breathe vapours and/or spray. Keep away from sources of ignition — No smoking. Build up of highly flammable gasses involves an explosion risk. Vapours are

heavier than air. Build up (of gasses) in low areas involves risk of suffocation.

### 6.2. Environmental precautions

Environmental precautions : Avoid release of product into sewers, surface water and/or ground water. Waste product should not

be allowed to contaminate soil or water.

Other information : Notify authorities if any exposure to the general public or the environment occurs or is likely to

occur.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Collect spilled material in containers. Collect aerosol cans in an approved container. Do not pierce

aerosols. Wash away remainder with plenty of water and soap.

#### 6.4. Reference to other sections

Reference to other sections: See also section 8.

### SECTION 7 HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Handling : Handle in accordance with good occupational hygiene and safety practices in well-ventilated

areas. Important: Pressurized container; protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Keep away from sources of ignition — No smoking. Do not spray on a naked flame or any incandescent material. Do not spray near fire, sources of heat or live electrical equipment. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Do not breathe spray. Do not breathe vapour. Avoid contact with skin and eyes. Avoid splashing. Wear protective clothing.

### 7.2. Conditions for safe storage, including any incompatibilities

Product name : Shell Tyre Repair Page 4/14

Date of issue : 2022-04-08 Replaces issue dated : 2020-05-06 INFO CARE SDS



According to Regulation (EU) No 2020/878

### Kemetyl

Storage : Keep away from oxidizing agents. Keep frost-free, in a cool (< 35°), dry and well-ventilated place.

Protect from sunlight and keep away from heat.

Recommended packaging : Not applicable.

7.3. Specific end use(s)

Use : Use only as directed.

### SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

.

### 8.1. Control parameters

Occupational exposure limits

: Occupational exposure limits have not been established for this product. Derived no-effect levels (DNEL) have not been established for this product. Predicted no-effect concentrations (PNEC) have

not been established for this product.

### Workplace exposure limits (mg/m³):

Chemical name	Country	TWA 8 hour	STEL 15 min	Comments	Source
		(mg/m3)	(mg/m3)		
Dimethyl ether	EC	1920	-	-	
Dimethyl ether	GB	766	958	-	
n-Butyl acetate	GB	724	966	-	
Butanone	EC	600	900	-	
Butanone	GB	600	899	Skin; BMGV	
Acetone	EC	1210	-	-	
Acetone	GB	1210	3620	-	

### Biological limit values (BMGV):

Substance	Country	Determinant		Specimen/Sampling
				Time/Remarks
			None known.	

Abbreviations BMG-list : B = Blood. U = Urine. b = At the end of the period of exposure. d = pre-shift.

Source : EH40/2005 (Fourth edition, 2020).

### Derived no-effect level (DNEL) for workers:

Chemical name	Route of	DNEL, short-t	DNEL, short-term D		DNEL, long-term	
	exposure					
	•	Local effect	Systemic effect	Local effect	Systemic effect	
Dimethyl ether	Inhalation				1894 mg/m3	
n-Butyl acetate	Inhalation	600 mg/m3	600 mg/m3	300 mg/m3	300 mg/m3	
	Dermal		11 mg/kg bw		11 mg/kg bw/day	
Butanone	Dermal				1161 mg/kg bw/day	
	Inhalation				600 mg/m3	
Acetone	Dermal				186 mg/kg bw/day	
	Inhalation			2420 mg/m3	1210 mg/m3	
Alkanes, C14-17, chloro	Inhalation				6,7 mg/m3	
	Dermal				47,9 mg/kg bw/day	

### Derived no-effect level (DNEL) for consumers:

Chemical name	Route of	DNEL, short-t	DNEL, short-term		m
	exposure				
		Local effect	Systemic effect	Local effect	Systemic effect
Dimethyl ether	Inhalation				471 mg/m3
n-Butyl acetate	Inhalation Dermal Oral	300 mg/m3	300 mg/m3 6 mg/kg bw 2 mg/kg bw	35.7 mg/m3	35.7 mg/m3 6 mg/kg bw/day 2 mg/kg bw/day

Product name : Shell Tyre Repair Page 5/14

Date of issue : 2022-04-08 Replaces issue dated : 2020-05-06 INFO CARE SDS



According to Regulation (EU) No 2020/878

### Kemety

Butanone	Dermal	412 mg/kg bw/day
	Inhalation	106 mg/m3
	Oral	31 mg/kg bw/day
Acetone	Dermal	62 mg/kg bw/day
	Inhalation	200 mg/m3
	Oral	62 mg/kg bw/day
Alkanes, C14-17, chloro	Inhalation	2 mg/m3
	Dermal	28,75 mg/kg bw/day
	Oral	0,58 mg/kg bw/day

### Predicted no-effect concentration (PNEC):

Chemical name	Route of exposure	Fresh water	Marine water	
Dimethyl ether	Water	0,155 mg/l	0,016 mg/l	i
	Sediment	0,681 mg/kg	0,069 mg/kg	
	Intermittent water			1,549 mg/l
	STP			160 mg/l
	Soil			0,045 mg/kg
n-Butyl acetate	Water	0,18 mg/l	0,015 mg/l	
	Sediment	0,981 mg/kg	0,0981 mg/kg	
	Intermittent water			0,36 mg/l
	STP			35,6 mg/l
	Soil			0,0903 mg/kg
Butanone	Water	55,8 mg/l	55,8 mg/l	
	Sediment	284,74 mg/kg	284,7 mg/kg	
	Intermittent water			55,8 mg/l
	STP			709 mg/l
	Soil			22,5 mg/kg
	Oral			1000 mg/kg food
Acetone	Water	10,6 mg/l	1,06 mg/l	
	Sediment	30,4 mg/kg	3,04 mg/kg	
	Intermittent water			21 mg/l
	STP			100 mg/l
	Soil			29,5 mg/kg
Alkanes, C14-17, chloro	Water	0,001 mg/l	0,002 mg/l	
, ,	Sediment	13 mg/kg	2,6 mg/kg	
	STP		, - 19.119	80 mg/l
	Soil			11,9 mg/kg
	Oral			10 mg/kg food

### 8.2. Exposure controls

Engineering measures : Use only in well-ventilated areas. Comply with standard precautionary measures for working

with chemicals. See Directive 2004/37/EG on the protection of workers from the risks related to

exposure to carcinogens or mutagens at work. May cause harm to breast-fed children.

Hygienic measures : When using do not eat, drink or smoke.

### Personal protective equipment:

The efficiency of personal protective equipment depends among other things on temperature and degree of ventilation. Always get professional advice for the particular local situation.

Body protection : Use of specific protective industrial clothing is not required for momentary use. Wear suitable

protective clothing, overalls or suit, and similar boots in accordance with EN 365/367 resp. 345 in case of frequent or prolonged use and in case of large scale exposure. Suitable material: butyl.

Indication of permeation breakthrough time: 1 hour.

Respiratory protection : Take care of sufficient ventilation. Wear suitable respiratory protection in case of large scale

exposure. Suitable: gas filter type A (brown), class I or higher on e.g. a facemask in accordance

with EN 140.

Product name : Shell Tyre Repair Page 6/14

Date of issue : 2022-04-08 Replaces issue dated : 2020-05-06 INFO CARE SDS



According to Regulation (EU) No 2020/878

Hand protection

: Under normal conditions of use specific gloves are not required. Wear appropriate gloves in case of frequent or prolonged use and in case of large scale exposure. Suitable material: butyl. ± 0,5 mm.

Pressurised container: May burst if heated.

Indication of permeation breakthrough time: 1 hour.

Eye protection : Wear appropriate safety glasses with side shields, in accordance with EN 166, when there is

danger of possible eye contact.

### SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state : Aerosol.
Colour : White.

Odour : Characteristic.
Odour threshold : Not known.

pH : Not applicable. Waterfree product.

Solubility in water : Active ingredients not soluble. Propellant(s) soluble.

Partition coefficient (n-oc- : Not known. Not measured. Not relevant for mixtures.

tanol/water)

Flash point : Not applicable. Not measurable.

Flammability (solid, gas) : Extremely flammable. Ignition distance and time equivalent needed to achieve ignition: Not

measured.

Auto ignition temperature : Not applicable. Aerosol container explodes before reaching the auto-ignition point.

Boiling point/boiling range : Not known. Not measurable.

Melting point/melting range : < 0 °C

Explosive properties :

Explosion limits (% in air) : 1,2 - 18,6

Oxidising properties : Not applicable. Does not contain oxidizing substances.

Decomposition temperature : Not applicable. Aerosol explodes before reaching the decomposition temperature.

Viscosity (20°C) : Not known. Not measurable. Viscosity (40°C) : Not known. Not measurable.

Vapour pressure (20°C) : 350000 Pa

Relative vapour density : > 1 (air = 1)

Relative density (20°C) : 0,79 g/ml

Particle characteristics : Not applicable. Liquid.

9.2. Other information

Other information : Not relevant.

### SECTION 10 STABILITY AND REACTIVITY

10.1. Reactivity

Reactivity : See sub-sections below.

10.2. Chemical stability

Stability : Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactivity : No other hazardous reactions known.

10.4. Conditions to avoid

Conditions to avoid : Keep away from sources of ignition and sources of heat. See section 7.

Product name : Shell Tyre Repair Page 7/14

Date of issue : 2022-04-08 Replaces issue dated : 2020-05-06 INFO CARE SDS



According to Regulation (EU) No 2020/878

### 10.5. Incompatible materials

Materials to avoid : Not applicable.

### 10.6. Hazardous decomposition products

Hazardous decomposition : May include and are not limited to: Hydrogen halogenide(s) (e.g. HF, HCI).

products

#### **SECTION 11 TOXICOLOGICAL INFORMATION**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

No toxicological research has been carried out on this product.

Inhalation

: Calculated LC50: > 10 mg/l. Ingredients of unknown toxicity: 5 %. ATE: > 5 mg/l. Low toxicity. Not Acute toxicity

> classified - based on available data, the classification criteria are not met. May cause damage to organs. Target organ(s): Central nervous system. Effect(s): Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, lightheadedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness

Corrosion/irritation : May cause irritation to respiratory airways and coughing. Not classified - based on available data,

the classification criteria are not met.

: Does not contain substances classified as respiratory sensitiser. Not classified - based on available Sensitisation

data, the classification criteria are not met.

: Does not contain carcinogenic substances. Not classified - based on available data, the Carcinogenicity

classification criteria are not met. Does not contain carcinogenic substances.

Mutagenicity : Does not contain mutagenic substances. Not classified - based on available data, the classification

criteria are not met.

Skin contact

Acute toxicity : Calculated LD50: > 5000 mg/kg.bw. Ingredients of unknown toxicity: < 1 %. ATE: > 2000 mg/kg.bw.

Low toxicity. Not classified - based on available data, the classification criteria are not met.

Corrosion/irritation Slight irritation possible. Repeated exposure may cause skin dryness or cracking. Not classified -

based on available data, the classification criteria are not met.

Sensitisation Does not contain skin sensitisers. Not classified - based on available data, the classification criteria

are not met.

Mutagenicity Does not contain mutagenic substances. Not classified - based on available data, the classification

criteria are not met.

Eve contact

Corrosion/irritation : Irritant.

Ingestion

: Aerosol or mist: Ingestion is unlikely to occur. Calculated LD50: > 2382 mg/kg.bw. Ingredients of Acute toxicity

unknown toxicity: 31 %. ATE: > 2000 mg/kg.bw. Low toxicity. Not classified - based on available

data, the classification criteria are not met.

Not expected to be an aspiration hazard. Contains a substance/substances with an aspiration Aspiration

hazard. Not classified - based on available data, the classification criteria are not met.

Corrosion/irritation : Aerosol or mist: Ingestion is unlikely to occur. May cause a feeling of sickness, vomiting and

diarrhoea.

Carcinogenicity : Aerosol or mist: Ingestion is unlikely to occur. Does not contain carcinogenic substances. Not

classified - based on available data, the classification criteria are not met.

: Aerosol or mist: Ingestion is unlikely to occur. Does not contain mutagenic substances. Not Mutagenicity

classified - based on available data, the classification criteria are not met.

Product name : Shell Tyre Repair Page 8/14 Date of issue : 2022-04-08 Replaces issue dated : 2020-05-06 **INFO CARE SDS** 



According to Regulation (EU) No 2020/878

Reprotoxicity

: Aerosol or mist: Ingestion is unlikely to occur. Development: Not expected to be reprotoxic. Development: Not classified - Based on available data, the classification criteria are not met. Fertility: not expected to be reprotoxic. Fertility: Not classified - based on available data, the classification criteria are not met.

### Toxicological information:

Chemical name	Property		Method	Test animal
n-Butyl acetate	NOAEL (inhalation)	2395 mg/m3		
	Skin sensitisation (	Not sensitizing		
	Skin irritation	Slightly irritant	OECD 404	Rabbit
	Eye irritation	Slightly irritant	OECD 405	Rabbit
	LC50 (inhalation)	> 21100 mg/m3	OECD 403	Rat
	Mutagenicity	Negative	OECD 471	Salmonella typhimurium
	LD50 (dermal)	> 14100 mg/kg bw	OECD 402	Rabbit
	LD50 (definal)	10700 mg/kg bw	0200 402	Rat
		> 3000 mg/m3	OECD 415	Rat
		Not genotoxic	OECD 473	T Cat
	NOAEL (developmental	_	OECD 473	Rat
	, ,	/ /230 mg/ms	OECD 414	Rai
Dutonono	toxicity, inh.)	0707 mm m/l/m hvv		Det
Butanone		2737 mg/kg bw		Rat
	LD50 (dermal)	6400 mg/kg bw		Rabbit
	LC50 (inhalation)	> 5000 mg/m3		Rat
	NOAEL (oral)	2500 mg/kg bw/d		Rat
	Skin sensitisation	Not sensitizing		Guinea pig
	Skin irritation	Moderately irritant		Rabbit
	Eye irritation	Highly irritant		Rabbit
	Genotoxicity - in vitro	Not genotoxic	OECD 473	<b> </b>
	Mutagenicity	Negative	OECD 471	Salmonella typhimurium
	Genotoxicity - in vivo	Not genotoxic	OECD 474	Mouse
	NOAEL (developmental	2955 mg/m3	OECD 414	Rat
	toxicity, inh.)			
	NOAEL (fertility) -	1644 mg/kg.d		Rat
	estimate			
	NOAEL (inhalation)	14790 mg/m3	OECD 413	Rat
		Not sensitizing		Guinea pig
	- estimate			
Acetone	Skin sensitisation	Not sensitizing	OECD 406	Guinea pig
	NOAEL (oral)	900 mg/kg bw/d	OECD 408	Rat
	NOAEL (inhalation)	22500 mg/m3		Rat
	Skin irritation	Non-irritant		Guinea pig
	Eye irritation	Moderately irritant	OECD 405	Rabbit
	LD50 (dermal)	> 15688 mg/kg bw		Rabbit
	NOAEL (fertility, oral)	900 mg/kg bw/d		Rat
	Mutagenicity	Negative	OECD 471	Salmonella typhimurium
	1 -	Not genotoxic	OECD 476	Mouse
	-	Not genotoxic	0200 470	Mouse
		5800 mg/kg bw		Rat
	NOEL (carcinogenicity,			T Cat
	inh.)	i vot caroniogenio		
	NOEL (carcinogenicity,	Not carcinogonio		
	oral)	inot carcinogenic		
	NOAEL (developmental	5300 mg/m3	OECD 414	Pot
		DOUD HIGHTIS	OECD 414	Rat
	toxicity, inh.)	Not coroin a sania		Mayoo
	NOEL (carcinogenicity,	inot carcinogenic		Mouse
	dermal)	I		

Product name : Shell Tyre Repair Page 9/14

Date of issue : 2022-04-08 Replaces issue dated : 2020-05-06 INFO CARE SDS



According to Regulation (EU) No 2020/878

### Kemetyl

	LC50 (inhalation) -	50100 mg/m3		Rat
	estimate			
Alkanes, C14-17, chloro	LD50 (oral)	> 4000 mg/kg bw		Rat
	NOAEL (oral)	10 mg/kg bw/d		Rat
	Skin sensitisation	Not sensitizing		Guinea pig
	Skin irritation	Slightly irritant	OECD 404	Rabbit
	Eye irritation	Slightly irritant		Rabbit
	NOAEL (development,	Not teratogenic		
	oral)			
	NOAEL (fertility) -	Not reprotoxic		
	estimate			
	LC50 (inhalation) -	> 3300 mg/m3	Read across	Rat
	estimate			
	NOAEL (fertility, oral)	100 mg/kg bw/d	OECD 421	Rat
İ	Mutagenicity	Negative	OECD 471	Salmonella typhimurium
	Genotoxicity - in vivo	> 5000 mg/kg bw/d	OECD 475	Rat

#### 11.2. Information on other hazards

Endocrine disrupting

properties

: Not applicable.

Other information : Not applicable.

### SECTION 12 ECOLOGICAL INFORMATION

12.1. Toxicity

No ecotoxicological research has been carried out on this product.

Ecotoxicity : Very toxic to aquatic organisms. Calculated LC50 (fish): 70 mg/l. Calculated EC50 (waterflea): < 1

mg/l. Contains 0 % of components with unknown hazards to the aquatic environment.

12.2. Persistence and degradability

12.3. Bioaccumulative potential

Bioaccumulative potential : Contains bioaccumulating substances.

12.4. Mobility in soil

Mobility : Not applicable

12.5. Results of PBT and vPvB assessment

PBT/vPvB assessment : Contains: Alkanes, C14-17, chloro

12.6. Endocrine disrupting properties

Endocrine disrupting

: Not applicable.

properties

12.7. Other adverse effects

Other adverse effects : Not applicable.

Ecological information:

Chemical name	Property		Method	Test animal
Alkanes, C14-17, chloro	EC50 (waterflea)	0,0059 mg/l	OECD 202	Daphnia magna
	LC50 (fish)	> 5000 mg/l	OECD 203	Alburnus alburnus

Product name : Shell Tyre Repair Page 10/14

Date of issue : 2022-04-08 Replaces issue dated : 2020-05-06 INFO CARE SDS



According to Regulation (EU) No 2020/878

	Ultimate aerobic	64 %	OECD 301 D	
	biodegradation (%) NOEC (waterflea) -	0,01 mg/l.d	OECD 202	Daphnia magna
	chronic			
Alkanes, C14-17, chloro	Log P(ow)	7,0000		
Alkanes, C14-17, chloro	BCF	1087		

#### **SECTION 13 DISPOSAL CONSIDERATIONS**

#### 13.1. Waste treatment methods

Product residues : Recyclable metal container. Do not puncture or burn even after use. Do not dispose empty pack

with waste produced by households. Containers may be recycled. Treat product residues and non-

empty pack as hazardous waste.

Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums. Additional warning

European waste catalogue : Dispose hazardous waste in accordance with Directive 91/689/EEC under acknowledgement of a

waste code according to Commission Decision 2000/532/EC to an official chemical waste depot.

: Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local legislation

Local regulations may be more stringent than regional or national requirements and must be

complied with.

#### **SECTION 14** TRANSPORT INFORMATION

14.1. UN number or ID number

: UN 1950 (For IATA only) ID 8000 UN nr.

14.2. UN proper shipping name

Transport name : AEROSOLS . For IATA only: CONSUMER COMMODITY Transport name (IMDG, : AEROSOLS . For IATA only: CONSUMER COMMODITY

IATA)

### 14.3/14.4/14.5. Transport hazard class(es)/Packing group/Environmental hazards

ADR/RID/ADN (road/railway/inland waterways)

Class : 2 Classification code : 5F Packaging group

: 2,1 + the "environmentally hazardous substance" mark. Danger label : D

Tunnel restriction

code





: Not intended for carriage by tank-vessels on inland waterways. Packagings with a quantity of 5 I or Other information

less for liquids or 5 kg, or less for solids need not be marked with the environmentally hazardous

substance mark.

IMDG (sea)

Class : 2,1 Packaging group

EmS (fire / spill) : F-D/S-U

Product name : Shell Tyre Repair Page 11/14 Date of issue : 2022-04-08 Replaces issue dated : 2020-05-06 **INFO CARE SDS** 



According to Regulation (EU) No 2020/878

### Kemetyl

Marine pollutant : Yes

Other information : Packagings with a quantity of 5 I or less for liquids or 5 kg, or less for solids need not be marked

with the environmentally hazardous substance mark.

IATA (air)

Class : 2,1 ERG code : 9L

### 14.6. Special precautions for user

Other information : Country specific variations may apply. It is possible that a "Limited Quantity" exemption applies

to the transport of this product. An IATA ID8000 Consumer Commodity package must bear an Air

Limited Quantity marking and a Class 9 hazard label.

### 14.7. Maritime transport in bulk according to IMO instruments

Marpol : Not intended to be carried in bulk according to International Maritime Organisation (IMO)

instruments. Packaged liquids are not considered bulk.

### **SECTION 15 REGULATORY INFORMATION**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Community regulations : Regulation (EU) No 2020/878 (REACH), Regulation (EC) No 1272/2008 (CLP), 75/324/EEC

(aerosols) and other regulations. Directive 2008/98/EC (waste).

: In the UK it is recommended that all aerosols should be labelled on the back with the warning about the dangers of volatile solvent abuse. The label should contain the badge 'Solvent Abuse Can Kill

Instantly' accompanied by the phrase 'Use only as directed'.

### 15.2. Chemical safety assessment

Chemical safety assessment

: Not applicable.

### SECTION 16 OTHER INFORMATION

### 16.1. Other information

The information in this safety data sheet is compiled in compliance with Regulation (EU) No 2020/878 dated 18 June 2020 and accurate to the best of our knowledge and experience at the date of issue specified. It is the user's obligation to use this product safely and to comply with all applicable laws and regulations concerning the use of the product. This safety data sheet complements the technical information sheets but does not replace them and offers no warranty with regard to product properties.

Users are also forewarned for any hazards involved when the product is used for other purposes than those for which it is designed.

Changed or new information with regard to the previous release is indicated with an asterisk (\*).

List of abbreviations and acronyms that could be (but not necessarily are) used in this safety data sheet:

ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE : Acute Toxicity Estimate

CLP : Classification, Labeling & Packaging

CMR : Carcinogenic, Mutagenic or toxic for Reproduction

EEC : European Economic Community

GHS : Globally Harmonized System of Classification and Labelling of Chemicals

IATA : International Air Transport Association IBC code : International Bulk Chemical Code

Product name : Shell Tyre Repair Page 12/14

Date of issue : 2022-04-08 Replaces issue dated : 2020-05-06 INFO CARE SDS



According to Regulation (EU) No 2020/878

### Kemetyl

IMDG : International Maritime Dangerous Goods Code LD50/LC50 : Lethal Dose/Concentration for 50% of a population

MAC : Maximum Allowable Concentration

MARPOL : International Convention for the Prevention of Pollution From Ships

NO(A)EL : No Observed (Adverse) Effect Level

OECD : Organisation for Economic Co-operation and Development

PBT : Persistent, Bioaccumulative and Toxic

PC : Chemical product category

PT : Product type

REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals

RID : Regulations concerning the International Carriage of Dangerous Goods by Rail

STP : Sewage Treatment Plant

SU : Sector of Use

TWA/STEL : Time-Weighted Average/Short Term Exposure Limit

UN : United Nations

UFI : Unique formula identifier
VOC : Volatile Organic Compounds

vPvB : Very Persistent and Very Bioaccumulative

Key data used to compile the Safety Data Sheet are from, but not limited to, one or more sources of information e.g. toxicological data from material suppliers, CONCAWE, IFRA, CESIO, Regulation EG 1272/2008, etc.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008:

Flam. Aer. 1 : Expert judgement.
Eye Irrit. 2 : Calculation method.
Lact. : Calculation method.
STOT SE 3 : Calculation method.
Aquatic Chronic 2 : Calculation method.
Aquatic Acute 1 : Calculation method.

#### Full text of hazard classes mentioned in section 3:

Flam. Gas 1 : Flammable gas, category 1.
Flam. Liq. 2 : Flammable liquid, category 2.
Flam. Liq. 3 : Flammable liquid, category 3.
Eye Irrit. 2 : Eye irritation, category 2.
Press. Gas : Gases under pressure.

Lact. : Reproductive toxicity, Additional category, Effects on or via lactation.

STOT SE 3 : Specific target organ toxicity after single exposure, category 3.

Aquatic Chronic 1 : Hazardous to the aquatic environment — Chronic category 1.

Aquatic Acute 1 : Hazardous to the aquatic environment — Acute category 1.

### Full text of H-phrases mentioned in section 3:

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H362 May cause harm to breast-fed children.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Advice on any training appropriate for workers: none.

Number format : "," used as decimal separator.

Product name : Shell Tyre Repair Page 13/14

Date of issue : 2022-04-08 Replaces issue dated : 2020-05-06 INFO CARE SDS



According to Regulation (EU) No 2020/878

End of safety data sheet.

Print date : 2022-04-20

Product name : Shell Tyre Repair Page 14/14

Date of issue : 2022-04-08 Replaces issue dated : 2020-05-06 INFO CARE SDS