

According to Regulation (EU) No 2020/878

## SECTION 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : SHELL LIQUID GREASE

Product code : CRX729, AT648I

1.2. Relevant identified uses of the substance or mixture and uses advised against

Application : SU21 Consumer product. PC24 Lubricants, greases, release agents.

1.3. Details of the supplier of the safety data sheet

Supplier : Kemetyl Polska Sp. z o. o.

Al. Jerozolimskie 146 02-305 Warszawa, Poland

Telephone : +48 22 822 5390
E-mail : msds@kemetyl.com
Website : www.kemetyl.com

1.4. Emergency telephone number

EMERGENCY TELEPHONE NUMBER, for DOCTORS/FIRE BRIGADE/POLICE only:

PL - Telephone : +48 22 822 5390 (During office hours only)

## SECTION 2 HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

CLP classification : Aerosols, category 1. Skin sensitization, category 1. Specific target organ toxicity after single

(1272/2008/EC) exposure, category 3. Hazardous to the aquatic environment — Chronic category 3.

Human health hazards : May cause drowsiness or dizziness. May cause an allergic skin reaction. Repeated exposure may

cause skin dryness or cracking. Exposure to high vapour concentrations may result in a narcotic effect. Use only as directed. Intentional misuse by deliberately concentrating and inhaling contents

can be harmful or fatal.

Physical/chemical hazards : Extremely flammable. Keep away from sources of ignition — No smoking. Do not spray on a

naked flame or any incandescent material. Do not spray near fire, sources of heat or live electrical equipment. Aerosol may explode from internal pressure build-up when exposed to temperatures

exceeding 50 °C.

Environmental hazards : Harmful to aquatic life with long lasting effects.

Other information : Caution: Do not breathe spray. Use only in well-ventilated areas. Spray in short intervals for a short

period only. Ventilate well after use. Harmful to house pets.

### 2.2. Label elements

Label elements (1272/2008/EC):

Hazard pictograms





Signal word : Danger

H- and P-phrases : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Product name : Shell Liquid Grease Page 1/13

Date of issue : 2022-03-28 Replaces issue dated : 2020-10-13 INFO CARE SDS



According to Regulation (EU) No 2020/878

H317 May cause an allergic skin reaction. May cause drowsiness or dizziness. H336

Harmful to aquatic life with long lasting effects. H412

EUH066 Repeated exposure may cause skin dryness or cracking.

If medical advice is needed, have product container or label at hand. P101

P102 Keep out of reach of children.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

Use only outdoors or in a well-ventilated area. P271

P280 gloves Wear protective gloves.

P405 Store locked up.

P501 Dispose of contents/container to an official chemical waste depot.

Labelling of packagings where the contents do not exceed 125 ml and it is technically impossible to list all phrases:

Hazard pictograms



Signal word Danger

H- and P-phrases : H222 Extremely flammable aerosol.

> Pressurised container: May burst if heated. H229 H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

**EUH066** Repeated exposure may cause skin dryness or cracking.

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P271 Use only outdoors or in a well-ventilated area.

P280 gloves Wear protective gloves.

P405 Store locked up.

P501 Dispose of contents/container to an official chemical waste depot.

Additional labelling (for all packaging sizes)

Contains: Pentane; Hydrocarbons, C9-11, n-alkanes, isoalkanes, cyclics, < 2% aromatics;

Naphthenic acids, zinc salts, basic.

## 2.3. Other hazards

Other information : The classification of this product is based on the non-aerosolised form of the mixture (on basis of

section 1.1.3.7. of Regulation (EC) No 1272/2008). Does not contain PBT or vPvB substances in

concentrations higher than 0,1%.

#### **SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**

### 3.2. Mixtures

Product name : Shell Liquid Grease Page 2/13 Date of issue : 2022-03-28 Replaces issue dated : 2020-10-13 **INFO CARE SDS** 



According to Regulation (EU) No 2020/878

## Kemetyl

Product description : Mixture.

### Information on hazardous substances:

Substance name	Concentration	CAS nr.	EC number	Remark	REACH nr.
	(w/w) (%)				
Butane	25 - < 50	106-97-8	203-448-7		01-2119474691-32
Pentane	10 - < 25	109-66-0	203-692-4		01-2119459286-30
Hydrocarbons, C9-11, n-alkanes,	10 - < 25		919-857-5		01-2119463258-33
isoalkanes, cyclics, < 2% aromatics					
Propane	2,5 - < 10	74-98-6	200-827-9		01-2119486944-21
Isobutane	2,5 - < 10	75-28-5	200-857-2		01-2119485395-27
Naphthenic acids, zinc salts, basic	0,1 - < 0,2	84418-50-8	282-762-6		01-2119988500-34

Substance name	Hazard Class	H-phrases	Pictograms	
Butane	Flam. Gas 1A; Press.	H220; H280	GHS02	
	Gas			
Pentane	Flam. Liq. 2; Asp. Tox.	H225; H304; H336;	GHS02; GHS07;	
	1; STOT SE 3; Aquatic	H411; EUH066	GHS08; GHS09	
	Chronic 2			
Hydrocarbons, C9-11, n-alkanes,	Flam. Liq. 3; Asp. Tox.	H226; H304; H336;	GHS02; GHS07;	
isoalkanes, cyclics, < 2% aromatics	1; STOT SE 3	EUH066	GHS08	
Propane	Flam. Gas 1A; Press.	H220; H280	GHS02	
	Gas			
Isobutane	Flam. Gas 1A; Press.	H220; H280	GHS02	
	Gas			
Naphthenic acids, zinc salts, basic	Skin Sens. 1A; Resp.	H317; H334; H412	GHS08	
	Sens. 1; Aquatic			
	Chronic 3			

Occupational exposure limit(s), if relevant, are listed in section 8.

Reference is made to chapter 16 for full text of each relevant H phrase.

## SECTION 4 FIRST-AID MEASURES

## 4.1. Description of first aid measures

First aid measures

Inhalation : Move victim into fresh air. Consult a doctor.

Skin contact : Take off contaminated clothing. Wash off skin with plenty of water and soap before product dries up.

Consult a doctor if irritation occurs.

Eye contact : Wash out with (lukewarm) water. Remove contact lenses. Consult a doctor if irritation persists.

Ingestion : Aerosol or mist: Ingestion is unlikely to occur.

## 4.2. Most important symptoms and effects, both acute and delayed

Effects and symptoms

Inhalation : May cause headache, drowsiness, dizziness and a feeling of sickness. May cause irritation to

respiratory airways and coughing.

Skin contact : Repeated exposure may cause skin dryness or cracking. May cause redness and irritation,

sensitisation. May produce an allergic reaction. May cause dry skin.

Eye contact : May cause stinging of eyes and redness.
Ingestion : Aerosol or mist: Ingestion is unlikely to occur.

## 4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians : None known.

Product name : Shell Liquid Grease Page 3/13

Date of issue : 2022-03-28 Replaces issue dated : 2020-10-13 INFO CARE SDS



According to Regulation (EU) No 2020/878

## SECTION 5 FIRE-FIGHTING MEASURES

\*

## 5.1. Extinguishing media

Extinguishing media

Suitable : Carbondioxide (CO2). Foam. Dry chemical. Water fog. Not suitable : Water jet. Use of heavy stream of water may spread fire.

## 5.2. Special hazards arising from the substance or mixture

Special exposure hazards : Aerosol may explode from internal pressure build-up when exposed to temperatures exceeding 50

°C. Do not expose emergency personnel to overheated aerosol containers. Water may be used to

cool container and prevent explosion of the aerosol.

Hazardous thermal decomposition products

: Carbon monoxide may be evolved if incomplete combustion occurs.

## 5.3. Advice for firefighters

Special protective equipment for fire-fighters

: Fight a fire where aerosols are involved from a protected position. Use adequate respiratory

equipment in case of insufficient ventilation.

## SECTION 6 ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions : Danger of slipping. Clean up spills immediately. Wear shoes with non-slip soles. Avoid contact

with spilled or released material. Do not breathe vapours and/or spray. Keep away from sources of ignition — No smoking. Build up of highly flammable gasses involves an explosion risk. Vapours are

heavier than air. Build up (of gasses) in low areas involves risk of suffocation.

### 6.2. Environmental precautions

Environmental precautions : Avoid release of product into sewers, surface water and/or ground water. Waste product should not

be allowed to contaminate soil or water.

Other information : Notify authorities if any exposure to the general public or the environment occurs or is likely to

occur.

## 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Collect spilled material in containers. Absorb residues in sand or other inert material. Collect

aerosol cans in an approved container. Do not pierce aerosols. Wash away remainder with plenty of

water and soap.

## 6.4. Reference to other sections

Reference to other sections: See also section 8.

## SECTION 7 HANDLING AND STORAGE

## 7.1. Precautions for safe handling

Product name : Shell Liquid Grease Page 4/13

Date of issue : 2022-03-28 Replaces issue dated : 2020-10-13 INFO CARE SDS



According to Regulation (EU) No 2020/878

Handling

: Handle in accordance with good occupational hygiene and safety practices in well-ventilated areas. Important: Pressurized container; protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Keep away from sources of ignition — No smoking. Do not spray on a naked flame or any incandescent material. Do not spray near fire, sources of heat or live electrical equipment. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Do not breathe spray. Do not breathe vapour. Avoid contact with skin and eyes. Avoid splashing. Wear protective clothing.

## 7.2. Conditions for safe storage, including any incompatibilities

Storage : Keep away from oxidizing agents. Keep frost-free, in a cool (< 35°), dry and well-ventilated place.

Protect from sunlight and keep away from heat.

Recommended packaging : Not applicable.

7.3. Specific end use(s)

Use : Use only as directed.

## SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1. Control parameters

Occupational exposure

limits

: Occupational exposure limits have not been established for this product. Derived no-effect levels (DNEL) have not been established for this product. Predicted no-effect concentrations (PNEC) have not been established for this product.

## Workplace exposure limits (mg/m³):

Chemical name	Country	TWA 8 hour	STEL 15 min	Comments	Source
		(mg/m3)	(mg/m3)		
Butane	GB	1450	1810	-	
Butane		1450	1810		MAC: MSDS Aeron
					Butane
Pentane	GB	1800	<b> -</b>	-	
Pentane	EC	3000	-	-	Directive 2006/15/EG
Hydrocarbons, C9-11, n-alkanes,		1200	-	-	CEFIC-HSPA
isoalkanes, cyclics, < 2% aromatics					
Propane		1800	<b> -</b>		MAC: BG, PL, CH, SL,
					etc
Isobutane		1900	2400		MAC: FI, BE, CH

## Derived no-effect level (DNEL) for workers:

Chemical name	Route of	DNEL, short-ter	DNEL, short-term		DNEL, long-term	
	exposure					
	,	Local effect	Systemic effect	Local effect	Systemic effect	
Pentane	Dermal				432 mg/kg bw/day	
	Inhalation		ĺ		3000 mg/m3	
Hydrocarbons, C9-11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Inhalation				1500 mg/m3	
	Dermal				300 mg/kg bw/day	
Naphthenic acids, zinc salts, basic	Inhalation				4,93 mg/m3	
	Dermal				1,4 mg/kg bw/day	

## Derived no-effect level (DNEL) for consumers:

Chemical name	Route of	DNEL, short-term		DNEL, long-term	
	exposure				
	×	Local effect	Systemic effect	Local effect	Systemic effect
Pentane	Dermal				214 mg/kg bw/day

Product name : Shell Liquid Grease Page 5/13

Date of issue : 2022-03-28 Replaces issue dated : 2020-10-13 INFO CARE SDS



According to Regulation (EU) No 2020/878

## Kemety

	Inhalation		643 mg/m3
	Oral		214 mg/kg bw/day
Hydrocarbons, C9-11, n-alkanes,	Dermal		300 mg/kg bw/day
isoalkanes, cyclics, < 2% aromatics			
	Inhalation		900 mg/m3
	Oral		300 mg/kg bw/day
Naphthenic acids, zinc salts, basic	Inhalation		0,87 mg/m3
	Dermal		0,5 mg/kg bw/day
	Oral		0,5 mg/kg bw/day

## Predicted no-effect concentration (PNEC):

Chemical name	Route of exposure	Fresh water	Marine water	
Pentane	Water	0,23 mg/l	0,23 mg/l	
	Sediment	1,2 mg/kg	1,2 mg/kg	
	Intermittent water			0,88 mg/l
	STP			3,6 mg/l
	Soil			0,55 mg/kg
Naphthenic acids, zinc salts, basic	Water	0.0206 mg/l	0.0061 mg/l	
	Sediment	117.8 mg/kg	56.5 mg/kg	
	STP			0.052 mg/l
	Soil			35.6 mg/kg

## 8.2. Exposure controls

Engineering measures : Use only in well-ventilated areas. Comply with standard precautionary measures for working with

chemicals.

Hygienic measures : When using do not eat, drink or smoke.

Personal protective equipment:

The efficiency of personal protective equipment depends among other things on temperature and degree of ventilation. Always get professional advice for the particular local situation.





Body protection : Wear appropriate protective clothing, overalls or suit, and similar boots in accordance with EN

365/367 resp. 345. Suitable material: nitril. Indication of permeation breakthrough time: 6 hours.

Respiratory protection : Take care of sufficient ventilation. Wear suitable respiratory protection in case of large scale

exposure. Suitable: gas filter type A (brown), class I or higher on e.g. a facemask in accordance

with EN 140.

Hand protection : Wear appropriate safety gloves in accordance with EN 374. Suitable material: nitril. ± 0,5 mm.

Indication of permeation breakthrough time: 6 hours.

Eye protection : Wear appropriate safety glasses when there is danger of possible eye contact.

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

## 9.1. Information on basic physical and chemical properties

Physical state : Aerosol.
Colour : Colourless.
Odour : Characteristic.
Odour threshold : Not known.

pH : Not applicable. Waterfree product.

Solubility in water : Active ingredients not soluble. Propellant(s) not soluble.

Product name : Shell Liquid Grease Page 6/13

Date of issue : 2022-03-28 Replaces issue dated : 2020-10-13 INFO CARE SDS



According to Regulation (EU) No 2020/878

## Kemetyl

Partition coefficient (n-oc-

: Not known.

Not measured. Not relevant for mixtures.

tanol/water)

Flash point

Not applicable.

Flammability (solid, gas) Extremely flammable. Not measurable.

Contains > 85% flammable components and has a heat of combustion >

30 kJ/q.

Auto ignition temperature Boiling point/boiling range

Not applicable. Not known.

Aerosol container explodes before reaching the auto-ignition point.

Not measurable.

Melting point/melting range:

< -20 °C

Explosive properties

Explosion limits (% in air)

0.6 - 10.9

Oxidising properties Decomposition temperature :

Not applicable. Not applicable.

Does not contain oxidizing substances. Aerosol explodes before reaching the decomposition temperature.

Pressurised container: May burst if heated.

Viscosity (20°C) Viscosity (40°C) Not known.

Not measurable.

Vapour pressure (20°C)

Not known.

Not measurable.

Relative vapour density

: 280000 Pa : >1

(air = 1)

Relative density (20°C) Particle characteristics

: 0,65 g/ml

: Not applicable.

Liquid.

9.2. Other information

Other information

: Not relevant.

#### **SECTION 10** STABILITY AND REACTIVITY

## 10.1. Reactivity

Reactivity : See sub-sections below.

10.2. Chemical stability

: Stable under normal conditions. Stability

# 10.3. Possibility of hazardous reactions

: No other hazardous reactions known. Reactivity

10.4. Conditions to avoid

Conditions to avoid : Keep away from sources of ignition and sources of heat. See section 7.

10.5. Incompatible materials

Materials to avoid : Not applicable.

## 10.6. Hazardous decomposition products

Hazardous decomposition : Not known.

products

#### **SECTION 11 TOXICOLOGICAL INFORMATION**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

No toxicological research has been carried out on this product. Inhalation

Product name : Shell Liquid Grease Page 7/13 Date of issue : 2022-03-28 Replaces issue dated : 2020-10-13 **INFO CARE SDS** 



According to Regulation (EU) No 2020/878

Acute toxicity	: Calculated LC50: > 10 mg/l. Ingredients	of unknown toxicity: < 1 %. ATE:	> 5 mg/l. Low toxicity. Not
----------------	---	----------------------------------	-----------------------------

classified - based on available data, the classification criteria are not met. May cause damage to organs. Target organ(s): Central nervous system. Effect(s): Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, lightheadedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness

and death.

Corrosion/irritation : May cause irritation to respiratory airways and coughing. Not classified - based on available data,

the classification criteria are not met.

Sensitisation : Does not contain substances classified as respiratory sensitiser. Not classified - based on available

data, the classification criteria are not met.

Carcinogenicity : Not expected to be carcinogenic. Not classified - based on available data, the classification criteria

are not met.

Mutagenicity : Does not contain mutagenic substances. Not classified - based on available data, the classification

criteria are not met.

Skin contact

Acute toxicity : Calculated LD50: > 5000 mg/kg.bw. Ingredients of unknown toxicity: < 1 %. ATE: > 2000 mg/kg.bw.

Low toxicity. Not classified - based on available data, the classification criteria are not met.

Corrosion/irritation : Slight irritation possible. Repeated exposure may cause skin dryness or cracking. Not classified -

based on available data, the classification criteria are not met.

Sensitisation : May cause sensitisation by skin contact. May produce an allergic reaction.

Mutagenicity : Does not contain mutagenic substances. Not classified - based on available data, the classification

criteria are not met.

Eye contact

Corrosion/irritation : Slight irritation possible. Not classified - based on available data, the classification criteria are not

met.

Ingestion

Acute toxicity : Aerosol or mist: Ingestion is unlikely to occur. Calculated LD50: > 1175 mg/kg.bw. Ingredients of

unknown toxicity: < 1 %. ATE: > 2000 mg/kg.bw. Low toxicity. Not classified - based on available

data, the classification criteria are not met.

Aspiration : Aerosol or mist: Ingestion is unlikely to occur. Not classified - based on available data, the

classification criteria are not met.

Corrosion/irritation : Aerosol or mist: Ingestion is unlikely to occur. May cause a feeling of sickness, stomachache,

vomiting and diarrhoea.

Carcinogenicity : Aerosol or mist: Ingestion is unlikely to occur. Not expected to be carcinogenic. Not classified -

based on available data, the classification criteria are not met.

Mutagenicity : Aerosol or mist: Ingestion is unlikely to occur. Does not contain mutagenic substances. Not

classified - based on available data, the classification criteria are not met.

Reprotoxicity : Aerosol or mist: Ingestion is unlikely to occur. Development: Not expected to be reprotoxic.

Development: Not classified - Based on available data, the classification criteria are not met. Fertility: not expected to be reprotoxic. Fertility: Not classified - based on available data, the

classification criteria are not met

## Toxicological information:

Chemical name	Property		Method	Test animal
Pentane	Skin irritation	Mildly irritant	OECD 404	Rabbit
	Skin sensitisation	Not sensitizing	OECD 406	Guinea pig
	NOAEL (development,	1000 mg/kg bw/d	OECD 414	Rat
	oral)			
	LC50 (inhalation)	> 20000 mg/m3		Rat
	Eye irritation	Slightly irritant		Rabbit
	Mutagenicity	Negative	OECD 471	Salmonella typhimurium
	LD50 (oral)	> 2000 mg/kg bw		Rat
	NOAEL (inhalation)	> 20000 mg/m3	OECD 413	Rat
	NOAEL (fertility, inh.)	24080 mg/m3	<b> </b>	Rat

Product name : Shell Liquid Grease Page 8/13

Date of issue : 2022-03-28 Replaces issue dated : 2020-10-13 INFO CARE SDS



According to Regulation (EU) No 2020/878

## Kemetyl

	Skin irritation	Non-irritant		Human
Hydrocarbons, C9-11, n-alkanes,	NOAEL (oral) -	> 1000 mg/kg bw/d	OECD 422	Rat
isoalkanes, cyclics, < 2% aromatics	estimate			
	Genotoxicity - estimate	Not genotoxic	OECD 476	Mouse
	NOEL (carcinogenicity)	Not carcinogenic	OECD 453	Rat
	- estimate			
	LD50 (dermal) -	> 5000 mg/kg bw	OECD 402	Rabbit
	estimate			
	LD50 (oral) - estimate	> 5000 mg/kg bw	OECD 401	Rat
	LC50 (inhalation) -	> 5000 mg/m3	OECD 403	Rat
	estimate			
	Skin irritation - estimate	Non-irritant	OECD 404	Rabbit
	Eye irritation - estimate	Non-irritant	OECD 405	Rabbit
	Skin sensitisation -	Not sensitizing	OECD 406	Guinea pig
	estimate			
	NOAEL (inhalation) -	> 1160 mg/m3	OECD 413	Rat
	estimate			
	NOAEL (fertility) -	> 1000 mg/kg.d	OECD 421	Rat
	estimate			
	NOAEL (development)	Not teratogenic	OECD 414	Rat
	- estimate			
Naphthenic acids, zinc salts, basic	LD50 (oral)	> 2000 mg/kg bw	OECD 423	Rat
	LC50 (inhalation)	420 mg/m3	OECD 403	Rat
	LC50 (inhalation) -	> 5000 mg/m3		
	estimate			
	LD50 (dermal)	> 2000 mg/kg bw	OECD 402	Rabbit
	Skin sensitisation	Sensitizing.	OECD 406	Guinea pig

## 11.2. Information on other hazards

Endocrine disrupting

properties

: Not applicable.

Other information

: Not applicable.

# SECTION 12 ECOLOGICAL INFORMATION

## 12.1. Toxicity

No ecotoxicological research has been carried out on this product.

Ecotoxicity : Harmful to aquatic organ

: Harmful to aquatic organisms. Calculated LC50 (fish): 24 mg/l. Calculated EC50 (waterflea): 15 mg/l. Contains 0 % of components with unknown hazards to the aquatic environment. May form an oil film on the water surface causing a decline in oxygen content with possible adverse effects for

aquatic organisms.

# 12.2. Persistence and degradability

Persistence – degradability: May cause long-term adverse effects in the aquatic environment.

# 12.3. Bioaccumulative potential

Bioaccumulative potential : No specific information known.

12.4. Mobility in soil

Mobility : Not applicable

## 12.5. Results of PBT and vPvB assessment

Product name : Shell Liquid Grease Page 9/13
Date of issue : 2022-03-28 Replaces issue dated : 2020-10-13 INFO CARE SDS



According to Regulation (EU) No 2020/878

## Kemetyl

PBT/vPvB assessment : Does not contain PBT or vPvB substances in concentrations higher than 0,1%.

## 12.6. Endocrine disrupting properties

**Endocrine disrupting** 

: Not applicable.

properties

## 12.7. Other adverse effects

Other adverse effects : Not applicable.

### Ecological information:

Chemical name	Property		Method	Test animal
Pentane	Ultimate aerobic biodegradation (%)	87 %	OECD 301 F	
	IC50 (algea)	10,7 mg/l	OECD 201	Selenastrum capricornutum
İ	EC50 (waterflea)	2,7 mg/l		Daphnia magna
	LC50 (fish)	4,26 mg/l	OECD 203	Oncorhynchus mykiss
Pentane	Log P(ow)	3,45		
Pentane	BCF	171		

#### **SECTION 13 DISPOSAL CONSIDERATIONS**

### 13.1. Waste treatment methods

Product residues : Recyclable metal container. Do not puncture or burn even after use. Do not dispose empty pack

with waste produced by households. Containers may be recycled. Treat product residues and non-

empty pack as hazardous waste.

Additional warning Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums.

Waste water discharge

Do not dispose into the environment, in drains or in water courses.

European waste catalogue : Dispose hazardous waste in accordance with Directive 91/689/EEC under acknowledgement of a

waste code according to Commission Decision 2000/532/EC to an official chemical waste depot. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local legislation

Local regulations may be more stringent than regional or national requirements and must be

complied with.

#### **SECTION 14** TRANSPORT INFORMATION

## 14.1. UN number or ID number

UN nr. : UN 1950 (For IATA only) ID 8000

## 14.2. UN proper shipping name

: AEROSOLS . For IATA only: CONSUMER COMMODITY Transport name : AEROSOLS . For IATA only: CONSUMER COMMODITY Transport name (IMDG,

IATA)

## 14.3/14.4/14.5. Transport hazard class(es)/Packing group/Environmental hazards

ADR/RID/ADN (road/railway/inland waterways)

: 2 Class : 5F Classification code Packaging group : -Danger label : 2,1

Product name : Shell Liquid Grease Page 10/13 Date of issue : 2022-03-28 Replaces issue dated : 2020-10-13 **INFO CARE SDS** 



According to Regulation (EU) No 2020/878

Tunnel restriction

: D

code



Other information : Not intended for carriage by tank-vessels on inland waterways.

IMDG (sea)

Class : 2,1 Packaging group : -

EmS (fire / spill) : F - D / S - U

Marine pollutant : No

IATA (air)

Class : 2,1 ERG code : 9L

## 14.6. Special precautions for user

Other information : Country specific variations may apply. It is possible that a "Limited Quantity" exemption applies

to the transport of this product. An IATA ID8000 Consumer Commodity package must bear an Air

Limited Quantity marking and a Class 9 hazard label.

## 14.7. Maritime transport in bulk according to IMO instruments

Marpol : Not intended to be carried in bulk according to International Maritime Organisation (IMO)

instruments. Packaged liquids are not considered bulk.

## SECTION 15 REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Community regulations : Regulation (EU) No 2020/878 (REACH), Regulation (EC) No 1272/2008 (CLP), 75/324/EEC

(aerosols) and other regulations. Directive 2008/98/EC (waste).

: This product is exempted from classification as "May be fatal if swallowed and enters airways" on

basis of section 3.10.1.6.3. of Annex I of Regulation (EC) No 1272/2008.

: In the UK it is recommended that all aerosols should be labelled on the back with the warning about the dangers of volatile solvent abuse. The label should contain the badge 'Solvent Abuse Can Kill

Instantly' accompanied by the phrase 'Use only as directed'.

15.2. Chemical safety assessment

Chemical safety : Not applicable.

assessment

## SECTION 16 OTHER INFORMATION

# 16.1. Other information

The information in this safety data sheet is compiled in compliance with Regulation (EU) No 2020/878 dated 18 June 2020 and accurate to the best of our knowledge and experience at the date of issue specified. It is the user's obligation to use this product safely and to comply with all applicable laws and regulations concerning the use of the product. This safety data sheet complements the technical information sheets but does not replace them and offers no warranty with regard to product properties.

Product name : Shell Liquid Grease Page 11/13

Date of issue : 2022-03-28 Replaces issue dated : 2020-10-13 INFO CARE SDS



According to Regulation (EU) No 2020/878

## Kemetyl

Users are also forewarned for any hazards involved when the product is used for other purposes than those for which it is designed.

Changed or new information with regard to the previous release is indicated with an asterisk (\*).

List of abbreviations and acronyms that could be (but not necessarily are) used in this safety data sheet:

ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE : Acute Toxicity Estimate

CLP : Classification, Labeling & Packaging

CMR : Carcinogenic, Mutagenic or toxic for Reproduction

EEC : European Economic Community

GHS : Globally Harmonized System of Classification and Labelling of Chemicals

IATA : International Air Transport Association IBC code : International Bulk Chemical Code

IMDG : International Maritime Dangerous Goods Code LD50/LC50 : Lethal Dose/Concentration for 50% of a population

MAC : Maximum Allowable Concentration

MARPOL : International Convention for the Prevention of Pollution From Ships

NO(A)EL : No Observed (Adverse) Effect Level

OECD : Organisation for Economic Co-operation and Development

PBT : Persistent, Bioaccumulative and Toxic

PC : Chemical product category

PT : Product type

REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals

RID : Regulations concerning the International Carriage of Dangerous Goods by Rail

STP : Sewage Treatment Plant

SU : Sector of Use

TWA/STEL : Time-Weighted Average/Short Term Exposure Limit

UN : United Nations

UFI : Unique formula identifier
VOC : Volatile Organic Compounds

vPvB : Very Persistent and Very Bioaccumulative

Key data used to compile the Safety Data Sheet are from, but not limited to, one or more sources of information e.g. toxicological data from material suppliers, CONCAWE, IFRA, CESIO, Regulation EG 1272/2008, etc.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008:

Flam. Aer. 1 : Expert judgement.
Skin Sens. 1/1A/1B : Calculation method.
STOT SE 3 : Calculation method.
Aquatic Chronic 3 : Calculation method.

Full text of hazard classes mentioned in section 3:

Flam. Gas 1 : Flammable gas, category 1.
Flam. Liq. 2 : Flammable liquid, category 2.
Flam. Liq. 3 : Flammable liquid, category 3.
Resp. Sens. 1 : Respiratory sensitization, category 1.
Skin Sens. 1/1A/1B : Skin sensitization, category 1/1A/1B.

Press. Gas : Gases under pressure.

STOT SE 3 : Specific target organ toxicity after single exposure, category 3.

Asp. Tox. 1 : Aspiration hazard, category 1.

Aquatic Chronic 2 : Hazardous to the aquatic environment — Chronic category 2. Aquatic Chronic 3 : Hazardous to the aquatic environment — Chronic category 3.

Full text of H-phrases mentioned in section 3:

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.

Product name : Shell Liquid Grease Page 12/13

Date of issue : 2022-03-28 Replaces issue dated : 2020-10-13 INFO CARE SDS



According to Regulation (EU) No 2020/878

## Kemetyl

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Advice on any training appropriate for workers: none.

Number format : "," used as decimal separator.

End of safety data sheet.

Print date : 2022-04-05

Product name : Shell Liquid Grease Page 13/13

Date of issue : 2022-03-28 Replaces issue dated : 2020-10-13 INFO CARE SDS