

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : Shell Motor Flush

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Intended for general public  
Use of the substance/mixture : crankcase cleaner

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

Kemetyl Kimya San.Tic.Ltd.Şti.  
Küçükbakkalköy Mahallesi Dereboyu Caddesi No:3A Brandium AVYM R/5 Blok K:13 D:82  
Ataşehir, İstanbul  
T +90-216 455 1641 - 42  
[salesKTR@kemetyl.com](mailto:salesKTR@kemetyl.com) - [www.kemetyl.com.tr](http://www.kemetyl.com.tr)

#### 1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Turkey	Ulusal Zehir Merkezi (UZEM) Refik Saydam Hıfzıssıhha Merkezi Başkanlığı	Cemal Gürsel Cd. No: 18 Sıhhiye Çankaya 06590 Ankara	114	Information is provided to public and medical personnel on poisoning incidents via 114.

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin sensitisation, Category 1 H317  
Germ cell mutagenicity, Category 1B H340  
Carcinogenicity, Category 1B H350  
Aspiration hazard, Category 1 H304

Full text of H statements : see section 16

##### Adverse physicochemical, human health and environmental effects

May cause cancer. May cause respiratory irritation. Causes skin irritation. May cause an allergic skin reaction. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects. May cause genetic defects.

# Shell Motor Flush

## Safety Data Sheet

according to Regulation (EU) 2015/830

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07 GHS08

Signal word (CLP) : Danger

Hazardous ingredients : Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts (Component; Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6 through C13 and boiling in the range of approximately 65°C to 230°C (149°F to 446°F).]; Lubricating oils; Baseoil— unspecified; [A complex combination of hydrocarbons obtained from solvent extraction and dewaxing processes. It consists predominantly of saturated hydrocarbons having carbon numbers in the range C15 through C50.]

Hazard statements (CLP) : H304 - May be fatal if swallowed and enters airways.  
H317 - May cause an allergic skin reaction.  
H340 - May cause genetic defects.  
H350 - May cause cancer.

Precautionary statements (CLP) : P101 - If medical advice is needed, have product container or label at hand.  
P102 - Keep out of reach of children.  
P201 - Obtain special instructions before use.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
P301+P310+P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.  
P308+P313 - IF exposed or concerned: Get medical advice/attention.

Child-resistant fastening : Applicable

Tactile warning : Applicable

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]

# Shell Motor Flush

## Safety Data Sheet

according to Regulation (EU) 2015/830

Lubricating oils; Baseoil— unspecified; [A complex combination of hydrocarbons obtained from solvent extraction and dewaxing processes. It consists predominantly of saturated hydrocarbons having carbon numbers in the range C15 through C50.]	(CAS-No.) 74869-22-0 (EC-No.) 278-012-2 (EC Index-No.) 649-484-00-0	65 - 80	Carc. 1B, H350
Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6 through C13 and boiling in the range of approximately 65°C to 230°C (149°F to 446°F).]	(CAS-No.) 64742-48-9 (EC-No.) 265-150-3 (EC Index-No.) 649-327-00-6	5 - 20	Carc. 1B, H350 Muta. 1B, H340 Asp. Tox. 1, H304
Benzene, mono-C10-13-alkyl derivs., fractionation bottoms, heavy ends, sulfonated, calcium salts (Component	(CAS-No.) 148520-84-7	0.8 - 2	Skin Sens. 1B, H317
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts (Component	(CAS-No.) 70024-69-0 (EC-No.) 274-263-7	0.2 – 0.5	Skin Sens. 1B, H317
naphthalene substance with a Community workplace exposure limit	(CAS-No.) 91-20-3 (EC-No.) 202-049-5 (EC Index-No.) 601-052-00-2	0.001 – 0.05	Carc. 2, H351 Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
1,2,4-trimethylbenzene substance with a Community workplace exposure limit	(CAS-No.) 95-63-6 (EC-No.) 202-436-9 (EC Index-No.) 601-043-00-3	0.001 – 0.05	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Aquatic Chronic 2, H411
mesitylene; 1,3,5-trimethylbenzene substance with a Community workplace exposure limit	(CAS-No.) 108-67-8 (EC-No.) 203-604-4 (EC Index-No.) 601-025-00-5 (REACH-no) 01-2119463878-19	0.003 – 0.009	Flam. Liq. 3, H226 STOT SE 3, H335 Aquatic Chronic 2, H411

Specific concentration limits:

Name	Product identifier	Specific concentration limits
------	--------------------	-------------------------------

# Shell Motor Flush

## Safety Data Sheet

according to Regulation (EU) 2015/830

Specific concentration limits:

Name	Product identifier	Specific concentration limits
mesitylene; 1,3,5-trimethylbenzene	(CAS-No.) 108-67-8 (EC-No.) 203-604-4 (EC Index-No.) 601-025-00-5 (REACH-no) 01-2119463878-19	( 25 ≤C < 100) STOT SE 3, H335

Full text of H-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : Call a physician immediately.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or a doctor. Call a poison center or a doctor if you feel unwell.
- First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse eyes with water as a precaution.
- First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately. If swallowed: rinse mouth. Do NOT induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after inhalation : May cause respiratory irritation.
- Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.
- Symptoms/effects after ingestion : Risk of lung oedema.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide. Dry powder.

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

# Shell Motor Flush

## Safety Data Sheet

according to Regulation (EU) 2015/830

### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.  
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Wear personal protective equipment. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

naphthalene (91-20-3)		
EU	Local name	Naphthalene
EU	IOELV TWA (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	10 ppm
EU	Notes	(Year of adoption 2010)
EU	Regulatory reference	COMMISSION DIRECTIVE 91/322/EEC; SCOEL Recommendations

# Shell Motor Flush

## Safety Data Sheet

according to Regulation (EU) 2015/830

<b>naphthalene (91-20-3)</b>		
Turkey	Local name	Naftalin
Turkey	OEL TWA (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
Turkey	OEL TWA (ppm)	10 ppm
Turkey	Regulatory reference	12 Ağustos 2013 Tarihli ve 28733 Sayılı Resmî Gazete

<b>1,2,4-trimethylbenzene (95-63-6)</b>		
EU	Local name	1,2,4-Trimethylbenzene
EU	IOELV TWA (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	20 ppm
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Turkey	Local name	1,2,4-Trimetilbenzen
Turkey	OEL TWA (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup>
Turkey	OEL TWA (ppm)	20 ppm
Turkey	Regulatory reference	12 Ağustos 2013 Tarihli ve 28733 Sayılı Resmî Gazete

<b>mesitylene; 1,3,5-trimethylbenzene (108-67-8)</b>		
EU	Local name	Mesitylene (Trimethylbenzenes)
EU	IOELV TWA (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	20 ppm
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Netherlands	Grenswaarde TGG 8H (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup>
Netherlands	Grenswaarde TGG 15MIN (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup>
Turkey	Local name	Mesitilen
Turkey	OEL TWA (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup> (Trimetilbenzen'ler)
Turkey	OEL TWA (ppm)	20 ppm (Trimetilbenzen'ler)
Turkey	Regulatory reference	12 Ağustos 2013 Tarihli ve 28733 Sayılı Resmî Gazete

**Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6 through C13 and boiling in the range of approximately 65°C to 230°C (149°F to 446°F).] (64742-48-9)**

EU	Local name	White spirit Type 3
EU	IOELV TWA (mg/m <sup>3</sup> )	116 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	20 ppm
EU	IOELV STEL (mg/m <sup>3</sup> )	290 mg/m <sup>3</sup>
EU	IOELV STEL (ppm)	50 ppm

# Shell Motor Flush

## Safety Data Sheet

according to Regulation (EU) 2015/830

**Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6 through C13 and boiling in the range of approximately 65°C to 230°C (149°F to 446°F).] (64742-48-9)**

EU	Notes	skin. (Year of adoption 2007)
EU	Regulatory reference	SCOEL Recommendations

### 8.2. Exposure controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### Personal protective equipment:

Protective clothing. Safety glasses. Gloves. Self-contained breathing apparatus.

#### Hand protection:

Protective gloves

#### Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):



Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: No data available
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available

# Shell Motor Flush

## Safety Data Sheet

according to Regulation (EU) 2015/830

Flash point	: > 100 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.8405 kg/m <sup>3</sup> 15°C
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 6.652 cSt 40°C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

**mesitylene; 1,3,5-trimethylbenzene (108-67-8)**



# Shell Motor Flush

## Safety Data Sheet

according to Regulation (EU) 2015/830

<b>mesitylene; 1,3,5-trimethylbenzene (108-67-8)</b>	
LD50 oral	5000 mg/kg bodyweight
LC50 inhalation rat (Dust/Mist - mg/l/4h)	24000 mg/l/4h

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Not classified  
Respiratory or skin sensitisation : May cause an allergic skin reaction.  
Germ cell mutagenicity : May cause genetic defects.  
Carcinogenicity : May cause cancer.  
Reproductive toxicity : Not classified

STOT-single exposure : Not classified  
STOT-repeated exposure : Not classified  
Aspiration hazard : May be fatal if swallowed and enters airways.

<b>Shell Motor Flush</b>	
Viscosity, kinematic	6.652 mm <sup>2</sup> /s 40°C

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects. Before neutralisation, the product may represent a danger to aquatic organisms.  
Hazardous to the aquatic environment, short-term (acute) : Not classified  
Hazardous to the aquatic environment, long-term (chronic) : Not classified

<b>mesitylene; 1,3,5-trimethylbenzene (108-67-8)</b>	
LC50 fish 1	3.48 mg/l
EC50 other aquatic organisms 1	50 mg/l EC50 waterflea (48 h)

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available

# Shell Motor Flush

## Safety Data Sheet

according to Regulation (EU) 2015/830

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

### SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.2. UN proper shipping name</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.3. Transport hazard class(es)</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.4. Packing group</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.5. Environmental hazards</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

#### 14.6. Special precautions for user

##### - Overland transport

Not regulated

##### - Transport by sea

Not regulated

##### - Air transport

Not regulated

##### - Inland waterway transport

Not regulated

##### - Rail transport

Not regulated

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

##### 15.1.2. National regulations

Regulation on Health and Safety Precautions When Working with Chemical Substances published in the Official Journal numbered 28733 on August 12, 2013

# Shell Motor Flush

## Safety Data Sheet

according to Regulation (EU) 2015/830

### Germany

Regulatory reference : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BlmSchV) : Is not subject of the 12. BlmSchV (Hazardous Incident Ordinance)

### Netherlands

SZW-lijst van kankerverwekkende stoffen : Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts (Component,Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6 through C13 and boiling in the range of approximately 65°C to 230°C (149°F to 446°F).],Lubricating oils; Baseoil— unspecified; [A complex combination of hydrocarbons obtained from solvent extraction and dewaxing processes. It consists predominantly of saturated hydrocarbons having carbon numbers in the range C15 through C50.] are listed

SZW-lijst van mutagene stoffen : Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts (Component,Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6 through C13 and boiling in the range of approximately 65°C to 230°C (149°F to 446°F).] are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

### Denmark

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product  
Pregnant/breastfeeding women working with the product must not be in direct contact with the product  
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

# Shell Motor Flush

## Safety Data Sheet

according to Regulation (EU) 2015/830

### Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
DPD	Dangerous Preparations Directive 1999/45/EC
DSD	Dangerous Substances Directive 67/548/EEC
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEL	No-Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
STP	Sewage treatment plant
TLM	Median Tolerance Limit
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative

### Data sources

: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

### Full text of H- and EUH-statements:

Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1

# Shell Motor Flush

## Safety Data Sheet

according to Regulation (EU) 2015/830

Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1B	Carcinogenicity, Category 1B
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Muta. 1B	Germ cell mutagenicity, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H340	May cause genetic defects.
H350	May cause cancer.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.