



Shell Premium Engine Coolant LongLife G13 RTU

Safety Data Sheet

according to Regulation (EU) 2015/830

Issue date: 12/3/2021 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Shell Premium Engine Coolant LongLife G13 RTU

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public

Use of the substance/mixture : Antifreeze / Coolant.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

Kemetyl Kimya San.Tic.Ltd.Şti.

Küçükbakkalköy Mahallesi Dereboyu Caddesi No:3A Brandium AVYM R/5 Blok K:13 D:82

Ataşehir, İstanbul

T +90-216 455 1641 - 42

salesKTR@kemetyl.com - www.kemetyl.com.tr

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Turkey	Ulusal Zehir Merkezi (UZEM) Refik Saydam Hıfzıssıhha Merkezi Başkanlığı	Cemal Gürsel Cd. No: 18 Sıhhiye Çankaya 06590 Ankara	114	Information is provided to public and medical personnel on poisoning incidents via 114.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Specific target organ toxicity — H373

Repeated exposure, Category 2

Full text of H-statements: see section 16

Adverse physicochemical, human health and environmental effects

May cause damage to organs through prolonged or repeated exposure.

Shell Premium Engine Coolant LongLife G13 RTU

Safety Data Sheet

according to Regulation (EU) 2015/830

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS08

Signal word (CLP) :

Warning

Hazardous ingredients :

Ethylene glycol

Hazard statements (CLP) :

H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements (CLP) :

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

P260 - Do not breathe dust/fume/gas/mist/vapours/spray.

Child-resistant fastening :

Not applicable

Tactile warning :

Applicable

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Ethylene glycol	(CAS-No.) 107-21-1 (EC-No.) 203-473-3 (EC Index-No.) 603-027-00-1 (REACH-no) 01-2119456816-28	34 – 80	Acute Tox. 4 (Oral), H302 STOT RE 2, H373
Glycerol (glycerin, glycerine)	(CAS-No.) 56-81-5 (EC-No.) 200-289-5	5 – 10	Not classified
Na-2-EH	(CAS-No.) 19766-89-3 (EC-No.) 243-283-8	0.1 – 3	Repr. 2, H361d

Full text of H- and EUH-statements: see section 16

Shell Premium Engine Coolant LongLife G13 RTU

Safety Data Sheet

according to Regulation (EU) 2015/830

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Get medical advice/attention if you feel unwell. Never give anything by mouth to an unconscious person. People with over sensibility problems are not allowed to work or be exposed to the product. In all cases of doubt, or when symptoms persist, seek medical attention.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Place the affected person in the recovery position. If breathing stops, give artificial respiration. If experiencing respiratory symptoms: Call a poison center or a doctor.
- First-aid measures after skin contact : After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Do not remove clothing if it sticks to the skin. Get medical attention if symptoms occur.
- First-aid measures after eye contact : Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minutes minimum). Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist if irritation persists.
- First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Do not induce vomiting. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂).
- Unsuitable extinguishing media : Strong water jet.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Contact with combustible material may cause fire.
- Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
- Reactivity in case of fire : At high temperature may liberate dangerous gases.
- Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

- Precautionary measures fire : Keep away from combustible materials. Approach from upwind.
- Firefighting instructions : Exercise caution when fighting any chemical fire. Do not enter fire area without proper protective equipment, including respiratory protection. Keep upwind. Use water spray or fog for cooling exposed containers. In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.
- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
- Other information : High temperature decomposition products are harmful by inhalation. Inhalation of vapour can cause breathing difficulties.

Shell Premium Engine Coolant LongLife G13 RTU

Safety Data Sheet

according to Regulation (EU) 2015/830

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Notify authorities if product enters sewers or public waters. Use care in walking on spilled material.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapours/spray. Evacuate unnecessary personnel. Mark out the contaminated area with signs and prevent access to unauthorized personnel. Avoid contact with skin, eyes and clothing.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection". Only qualified personnel equipped with suitable protective equipment may intervene.
Emergency procedures : Keep public away from danger area. Evacuate unnecessary personnel. Stop leak if safe to do so. Do not touch spilled material. Avoid contact with skin and eyes. Ventilate area. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter drains or water courses. Do not discharge into drains or waterways without neutralizing.

6.3. Methods and material for containment and cleaning up

For containment : Comply with the safety instructions.
Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Sweep or shovel spills into appropriate container for disposal. Minimise generation of dust.
Other information : Dispose of materials or solid residues at an authorized site. Dispose of contaminated materials in accordance with current regulations.

6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Ensure good ventilation of the work station.
Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid dust formation. Avoid prolonged and repeated contact with skin. Contaminated work clothing should not be allowed out of the workplace. Do not spray on an open flame or other ignition source.

Shell Premium Engine Coolant LongLife G13 RTU

Safety Data Sheet

according to Regulation (EU) 2015/830

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ensure adequate ventilation, especially in confined areas. Comply with applicable regulations.

Storage conditions : Store in a well-ventilated place. Keep cool.

Incompatible products : Strong acids. Strong bases. Strong oxidizing agents.

Incompatible materials : Extremely high or low temperatures.

Heat and ignition sources : Do not smoke. Keep away from sources of ignition. Keep away from heat and direct sunlight.

Information on mixed storage : Keep away from food, drink and animal feeding stuffs.

Storage area : Avoid: Extremely high or low temperatures. Heat and ignition sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station. Avoid contact with skin, eyes and clothing.

Personal protective equipment:

Protective clothing. Safety glasses. Gloves.

Hand protection:

Protective gloves. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Gloves must be replaced after each use and whenever signs of wear or perforation appear

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



Environmental exposure controls:

Avoid release to the environment.

Consumer exposure controls:

Do not eat, drink or smoke during use. Always wash hands after handling the product. Avoid contact with skin and eyes. Avoid contact during pregnancy/while nursing.

Shell Premium Engine Coolant LongLife G13 RTU

Safety Data Sheet

according to Regulation (EU) 2015/830

Other information:

Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: light red.
Odour	: slight.
Odour threshold	: No data available
pH	: 8.45
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: -37 °C
Boiling point	: 109 °C
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.08 kg/l
Solubility	: miscible in water.
Partition coefficient n-octanol/water (Log Pow)	: -1.36 Ethylene glycol -1.76 Glycerol
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

Shell Premium Engine Coolant LongLife G13 RTU

Safety Data Sheet

according to Regulation (EU) 2015/830

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified.

Shell Premium Engine Coolant LongLife G13 RTU	
LD50 oral rat	3696 mg/kg
LD50 oral	> 3500 mg/kg
LC50 Inhalation - Rat	2.5 mg/l
ATE CLP (vapours)	2.5 mg/l/4h
ATE CLP (dust,mist)	2.5 mg/l/4h

Ethylene glycol (107-21-1)	
LD50 oral rat	10600 mg/kg
LD50 oral	7712 mg/kg bodyweight
LD50 dermal	10600 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	> 2500 mg/l/4h

Glycerol (glycerin, glycerine) (56-81-5)	
LD50 oral rat	Animal: rat, Animal sex: female

Na-2-EH (19766-89-3)	
LD50 oral rat	2043 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1445 - 2890
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

Skin corrosion/irritation : Not classified
pH: 8.45

Shell Premium Engine Coolant LongLife G13 RTU

Safety Data Sheet

according to Regulation (EU) 2015/830

Serious eye damage/irritation	: Not classified pH: 8.45
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.

Ethylene glycol (107-21-1)

NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight/day
----------------------------	--------------------------

Na-2-EH (19766-89-3)

NOAEL (oral, rat, 90 days)	≈ 300 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test)
----------------------------	---

Aspiration hazard	: Not classified
-------------------	------------------

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

Shell Premium Engine Coolant LongLife G13 RTU

LC50 - Fish [1]	72860 mg/l
-----------------	------------

EC50 - Crustacea [1]	> 100 mg/l
----------------------	------------

Ethylene glycol (107-21-1)

LC50 - Fish [1]	72860 mg/l
-----------------	------------

EC50 - Other aquatic organisms [1]	> 100 mg/l EC50 waterflea (48 h)
------------------------------------	----------------------------------

EC50 - Other aquatic organisms [2]	6500 mg/l IC50 alga (72 h) mg/l
------------------------------------	---------------------------------

Glycerol (glycerin, glycerine) (56-81-5)

LC50 - Fish [1]	54000 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
-----------------	---

Na-2-EH (19766-89-3)

LC50 - Fish [1]	> 100 mg/l Test organisms (species): Oryzias latipes
-----------------	--

EC50 - Crustacea [1]	910 mg/l Test organisms (species): Daphnia magna
----------------------	--

EC50 72h - Algae [1]	49.3 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
----------------------	--

Shell Premium Engine Coolant LongLife G13 RTU

Safety Data Sheet

according to Regulation (EU) 2015/830

Na-2-EH (19766-89-3)

LOEC (chronic)	63 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	25 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Shell Premium Engine Coolant LongLife G13 RTU

Partition coefficient n-octanol/water (Log Pow)	-1.36 – -1.76
---	---------------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations. Waste Management Regulation published in the Official Journal numbered 29314 on April 2, 2015.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Completely empty the packaging prior to decontamination. Comply with applicable regulations for solid waste disposal.
Additional information	: Empty containers should be taken for recycling, recovery or waste in accordance with local regulation.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

Shell Premium Engine Coolant LongLife G13 RTU

Safety Data Sheet

according to Regulation (EU) 2015/830

14.6. Special precautions for user

- Overland transport

Not applicable

- Transport by sea

Not applicable

- Air transport

Not applicable

- Inland waterway transport

Not applicable

- Rail transport

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	Shell Premium Engine Coolant LongLife G13 RTU ; Ethylene glycol
--	---

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate

Shell Premium Engine Coolant LongLife G13 RTU

Safety Data Sheet

according to Regulation (EU) 2015/830

BCF	Bioconcentration factor
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
DPD	Dangerous Preparations Directive 1999/45/EC
DSD	Dangerous Substances Directive 67/548/EEC
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEL	No-Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
STP	Sewage treatment plant
TLM	Median Tolerance Limit
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative

Data sources : Classification according to Classification, Labelling and Packaging of Substances and Mixtures (SEA) Regulation published in the Official Journal numbered 28848 on December 11, 2013. ECHA (European Chemicals Agency). Supplier's safety documents.

Full text of H- and EUH-statements:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Repr. 2	Reproductive toxicity, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
H302	Harmful if swallowed.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

Shell Premium Engine Coolant LongLife G13 RTU

Safety Data Sheet

according to Regulation (EU) 2015/830

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.