



Shell Premium Engine Coolant NF RTU 50/50

Safety Data Sheet

according to Regulation (EU) 2015/830

Issue date: 7/12/2019 Revision date: 5/24/2021 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Shell Premium Engine Coolant NF RTU 50/50

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Professional use
coolant

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

Kemetyl Kimya San.Tic.Ltd.Şti.
Küçükbakkalköy Mahallesi Dereboyu Caddesi No:3A Brandium AVYM R/5 Blok K:13 D:82
Ataşehir, İstanbul
T +90-216 455 1641 - 42
salesKTR@kemetyl.com - www.kemetyl.com.tr

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Turkey	Ulusal Zehir Merkezi (UZEM) Refik Saydam Hıfzıssıhha Merkezi Başkanlığı	Cemal Gürsel Cd. No: 18 Sıhhiye Çankaya 06590 Ankara	114	Information is provided to public and medical personnel on poisoning incidents via 114.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4 H302

Specific target organ toxicity — H373

Repeated exposure, Category 2

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

May cause damage to organs through prolonged or repeated exposure. Harmful if swallowed.

Shell Premium Engine Coolant NF RTU 50/50

Safety Data Sheet

according to Regulation (EU) 2015/830

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07 GHS08

Signal word (CLP) : Warning

Hazardous ingredients : Ethylene glycol

Hazard statements (CLP) : H302 - Harmful if swallowed.
H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements (CLP) : P264 - Wash hands, forearms and face thoroughly after handling.
P314 - Get medical advice/attention if you feel unwell.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Ethylene glycol	(CAS-No.) 107-21-1 (EC-No.) 203-473-3 (EC Index-No.) 603-027-00-1 (REACH-no) 01-2119456816-28	45 – 50	Acute Tox. 4 (Oral), H302 STOT RE 2, H373
disodium tetraborate pentahydrate; borax pentahydrate substance listed as REACH Candidate (Disodium tetraborate, anhydrous)	(CAS-No.) 12179-04-3 (EC-No.) 215-540-4 (EC Index-No.) 005-011-02-9	1 – 2	Repr. 1B, H360FD

Specific concentration limits:

Name	Product identifier	Specific concentration limits
disodium tetraborate pentahydrate; borax pentahydrate	(CAS-No.) 12179-04-3 (EC-No.) 215-540-4 (EC Index-No.) 005-011-02-9	(6.5 ≤C < 100) Repr. 1B, H360FD

Full text of H-statements: see section 16

Shell Premium Engine Coolant NF RTU 50/50

Safety Data Sheet

according to Regulation (EU) 2015/830

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Call a poison center or a doctor if you feel unwell.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Wash skin with plenty of water.
- First-aid measures after eye contact : Rinse eyes with water as a precaution.
- First-aid measures after ingestion : Rinse mouth. Call a poison center or a doctor if you feel unwell. If swallowed: rinse mouth. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Foam. Carbon dioxide. Dry powder. Dry powder.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray.

Shell Premium Engine Coolant NF RTU 50/50

Safety Data Sheet

according to Regulation (EU) 2015/830

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ethylene glycol (107-21-1)		
EU	Local name	Ethylene glycol
EU	IOELV TWA (mg/m ³)	52 mg/m ³
EU	IOELV TWA (ppm)	20 ppm
EU	IOELV STEL (mg/m ³)	104 mg/m ³
EU	IOELV STEL (ppm)	40 ppm
EU	Notes	Skin
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Netherlands	Grenswaarde TGG 8H (mg/m ³)	52 mg/m ³
Netherlands	Grenswaarde TGG 15MIN (mg/m ³)	104 mg/m ³
Turkey	Local name	Etilen glikol
Turkey	OEL TWA (mg/m ³)	52 mg/m ³
Turkey	OEL TWA (ppm)	20 ppm
Turkey	OEL STEL (mg/m ³)	104 mg/m ³
Turkey	OEL STEL (ppm)	40 ppm
Turkey	Comments	Deri
Turkey	Regulatory reference	12 Ağustos 2013 Tarihli ve 28733 Sayılı Resmî Gazete

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protective equipment:

Protective clothing. Safety glasses. Gloves.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Shell Premium Engine Coolant NF RTU 50/50

Safety Data Sheet

according to Regulation (EU) 2015/830

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Blue.
Odour	: characteristic.
Odour threshold	: No data available
pH	: 7 – 10
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: -36 °C
Boiling point	: > 100 °C
Flash point	: > 125 °C
Auto-ignition temperature	: 400 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.04 – 1.09
Solubility	: Miscible; acetone, alcohol, water.
Partition coefficient n-octanol/water (Log Pow)	: -1.93
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Lower explosive limit (LEL)	: 4.9 vol %
Upper explosive limit (UEL)	: 14.6 vol %

Shell Premium Engine Coolant NF RTU 50/50

Safety Data Sheet

according to Regulation (EU) 2015/830

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

ATE CLP (oral)	1000 mg/kg bodyweight
----------------	-----------------------

Ethylene glycol (107-21-1)	
LD50 oral rat	10600 mg/kg
LD50 oral	7712 mg/kg bodyweight
LD50 dermal	10600 mg/kg bodyweight
LC50 inhalation rat (Dust/Mist - mg/l/4h)	> 2500 mg/l/4h

Skin corrosion/irritation : Not classified
pH: 7 – 10

Serious eye damage/irritation : Not classified
pH: 7 – 10

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Ethylene glycol (107-21-1)	
NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight/day

Shell Premium Engine Coolant NF RTU 50/50

Safety Data Sheet

according to Regulation (EU) 2015/830

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Ethylene glycol (107-21-1)

LC50 fish 1	72860 mg/l
-------------	------------

EC50 other aquatic organisms 1	> 100 mg/l EC50 waterflea (48 h)
--------------------------------	----------------------------------

EC50 other aquatic organisms 2	6500 mg/l IC50 alga (72 h) mg/l
--------------------------------	---------------------------------

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Shell Premium Engine Coolant NF RTU 50/50

Partition coefficient n-octanol/water (Log Pow)	-1.93
---	-------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Component

disodium tetraborate pentahydrate; borax pentahydrate (12179-04-3)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
--	---

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

Shell Premium Engine Coolant NF RTU 50/50

Safety Data Sheet

according to Regulation (EU) 2015/830

ADR	IMDG	IATA	ADN	RID
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

14.6. Special precautions for user

- Overland transport

Not applicable

- Transport by sea

Not applicable

- Air transport

Not applicable

- Inland waterway transport

Not applicable

- Rail transport

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains a substance on the REACH candidate list in concentration $\geq 0.1\%$ or with a lower specific limit:
Disodium tetraborate, anhydrous (EC 215-540-4, CAS 12179-04-3)

Contains no REACH Annex XIV substances

15.1.2. National regulations

Regulation on Health and Safety Precautions When Working with Chemical Substances published in the Official Journal numbered 28733 on August 12, 2013

Germany

Regulatory reference : WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BlmSchV) : Is not subject of the 12. BlmSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

Shell Premium Engine Coolant NF RTU 50/50

Safety Data Sheet

according to Regulation (EU) 2015/830

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid	: disodium tetraborate pentahydrate; borax pentahydrate is listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling	: disodium tetraborate pentahydrate; borax pentahydrate is listed
Denmark	
Danish National Regulations	: Young people below the age of 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
DPD	Dangerous Preparations Directive 1999/45/EC
DSD	Dangerous Substances Directive 67/548/EEC
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEL	No-Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic

Shell Premium Engine Coolant NF RTU 50/50

Safety Data Sheet

according to Regulation (EU) 2015/830

PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
STP	Sewage treatment plant
TLM	Median Tolerance Limit
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Full text of H- and EUH-statements:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Repr. 1B	Reproductive toxicity, Category 1B
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
H302	Harmful if swallowed.
H360FD	May damage fertility. May damage the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.