

Technical Data Sheet (TDS)

Shell Liquid Grease



Shell Liquid Grease is a multipurpose, white and long-lasting grease with excellent material compatibility.

Performance Features and Benefits

- Lubrication tasks during maintenance operations for instance hinges, joints, sliding rails etc., all surfaces that needs lubrication at home or work.
- Perfect insulation against dirt and humidity.
- Increases oxidation resistance and lubrication intervals.
- Offers perfect corrosion protection.
- It is highly compatible with plastics and has a neutral effect on painted surfaces.
- Does not contain silicon, resin or acid.

Typical Properties* ;

Density	ASTM 4052	0,67
pH, @20°C	ASTM D-1287	8,22
Color		Transparent yellow

*** All figures are typical values and do not constitute a specification.**

The content of this Technical Data Sheet has been prepared by taking into consideration the relevant international standards and the information contained in specifications of vehicle and equipment manufacturers. This Technical Data Sheet and the statements in content cannot be interpreted as a guarantee commitment in respect of product specifications or usage in any application.

It is the consumer's responsibility to use this product in accordance with its ordinary purpose and comply with the applicable laws and regulations. Kemetyl Kimya San. Tic. Ltd. Şti. shall not be held responsible for any claims or damages arising out of abnormal use, improper usage, use for the wrongful purposes or risks and consequences by the nature of product structure.

This Technical Data Sheet shall be valid on issue date. Right to amend information provided in content of this Technical Data Sheet without prior notice is reserved.