

# Technical Data Sheet (TDS)

## Shell Silicon Spray



Shell Silicon Spray provides long-lasting protection, cleanliness, maintenance, insulation and lubrication on plastic and rubber surfaces.

### Performance Features and Benefits

- Bumpers, slats, plastic rails, slots, door strips, rubber seals, rubber bellows and hoses are the main areas of use.
- Prevents wear of plastic and rubber parts, eliminates creaking sounds and noises.
- Eases assembly works. Improves the appearance of the materials it is applied.
- Protects vinyl and plastic coatings and electrical connections against humidity.
- It is antistatic.

### Typical Properties\* ;

Density	ASTM 4052	0,59
pH, @20°C	ASTM D-1287	8,31
Color		Transparent

**\* All figures are typical values and do not constitute a specification.**

*The content of this Technical Data Sheet has been prepared by taking into consideration the relevant international standards and the information contained in specifications of vehicle and equipment manufacturers. This Technical Data Sheet and the statements in content cannot be interpreted as a guarantee commitment in respect of product specifications or usage in any application.*

*It is the consumer's responsibility to use this product in accordance with its ordinary purpose and comply with the applicable laws and regulations. Kemetyl Kimya San. Tic. Ltd. Şti. shall not be held responsible for any claims or damages arising out of abnormal use, improper usage, use for the wrongful purposes or risks and consequences by the nature of product structure.*

*This Technical Data Sheet shall be valid on issue date. Right to amend information provided in content of this Technical Data Sheet without prior notice is reserved.*